

CHECK POINT 15400 APPLIANCE



CHECK POINT 15400 APPLIANCE

Large enterprise security,
performance and reliability

Product Benefits

- Extensible security protections with Advanced Threat Prevention
- High-availability options maximize uptime
- Centralized control and LOM improves serviceability
- High performance package optimizes platform performance
- Flexible I/O options

Product Features

- 2,600 SecurityPower™ Units
- 23 Gbps real-world firewall throughput
- 1.5 Gbps real-world threat prevention throughput
- Simple deployment and management
- Virtual Systems consolidates security onto one device
- High port density with 40 GbE option
- Redundant power supplies, fans and hard disk drives eliminate single point of failure

OVERVIEW

The Check Point 15400 security appliance is ideal for large enterprise networks and data centers that require exceptional performance and flexible I/O options in a compact form factor. The 15400 is a 2U appliance with three I/O expansion slots for high port capacity, redundant power supplies, 1 TB of disk space, and Lights-Out Management (LOM) for remote management. This powerful security appliance is optimized to deliver real-world threat prevention throughput of 1.5 Gbps to secure your critical assets and environments.

The 15400 appliance combines the most comprehensive security protections with purpose-built hardware to maximize uptime while delivering high-performance for safeguarding demanding enterprise and data center environments. With a redundant hard disk drive option, redundant fans, and power supplies, support for 40 GbE connectivity as well as Lights-Out-Management for complete serviceability and control, the Check Point 15400 appliance is designed to satisfy your enterprise security needs while future-proofing your security foundation to address tomorrow's trends and threats today.

COMPREHENSIVE THREAT PREVENTION

The rapid growth of malware, growing attacker sophistication and the rise of new unknown zero-day threats requires a different approach to keep enterprise networks and data secure. Check Point delivers fully integrated, comprehensive Threat Prevention to combat these emerging threats while reducing complexities and increasing operational efficiencies. The Check Point Threat Prevention solution includes powerful security features such as firewall, IPS, Anti-Bot, Antivirus, Application Control, and URL Filtering to combat known cyber-attacks and threats – now enhanced with the award-winning SandBlast™ Threat Emulation and Threat Extraction for complete protection against the most sophisticated threats and zero-day vulnerabilities.

ALL-INCLUSIVE SECURITY SOLUTIONS

Check Point 15400 Appliances offer a complete and consolidated security solution available in two complete packages:

- NGTP: prevent sophisticated cyber-threats with IPS, Application Control, Antivirus, Anti-Bot, URL Filtering and Email Security.
- NGTX: NGTP with SandBlast Zero-Day Protection, which includes Threat Emulation and Threat Extraction.

PREVENT KNOWN AND ZERO-DAY THREATS

The 15400 Appliance protects organizations from both known and unknown threats with Antivirus, Anti-Bot, SandBlast Threat Emulation (sandboxing), and SandBlast Threat Extraction technologies.

As part of the Check Point SandBlast Zero-Day Protection solution, the cloud-based Threat Emulation engine detects malware at the exploit phase, even before hackers can apply evasion techniques attempting to bypass the sandbox. Files are quickly quarantined and inspected, running in a virtual sandbox to discover malicious behavior before it enters your network. This innovative solution combines cloud-based CPU-level inspection and OS-level sandboxing to prevent infection from the most dangerous exploits, and zero-day and targeted attacks.

Furthermore, SandBlast Threat Extraction removes exploitable content, including active content and embedded objects, reconstructs files to eliminate potential threats, and promptly delivers sanitized content to users to maintain business flow.

	NGTP	NGTX
	Prevent known threats	Prevent known and zero-day attacks
Firewall	✓	✓
VPN (IPSec)	✓	✓
IPS	✓	✓
Application Control	✓	✓
Anti-Bot	✓	✓
Anti-Virus	✓	✓
URL Filtering	✓	✓
Threat Emulation	✗	✓
Threat Extraction	✗	✓

INCLUSIVE HIGH PERFORMANCE PACKAGE

Customers with high connection capacity requirements can purchase the affordable High Performance Package (HPP). This includes the appliance plus one 4x 10Gb SFP+ interface card, transceivers, 2x 1TB disk drives and 24 GB of memory for high connection capacity.

	Base	HPP	Max
1 GbE ports (Copper)	10	10	26
10 GbE ports (Fiber)	2	6	12
Transceivers (SR)	2	6	12
RAM	8GB	24GB	
HDD	1	2	
Power Supply Units	2	2	
Lights Out Management	Included	Included	

A RELIABLE SERVICEABLE PLATFORM

The Check Point 15400 appliance delivers business continuity and serviceability through features such as hot swappable redundant power supplies, optional hot-swappable redundant hard disk drives (RAID), redundant fans and an advanced LOM card for out-of-band management. Combined together, these features ensure a greater degree of business continuity and serviceability when these appliances are deployed in the customer's networks.

REMOTE MANAGEMENT AND MONITORING

A Lights-Out-Management (LOM) card provides out-of-band remote management to remotely diagnose, start, restart and manage the appliance from a remote location. Administrators can also use the LOM web interface to remotely install an OS image from an ISO file.

40 GbE CONNECTIVITY

High speed connections are essential in modern enterprise and data center environments, especially those with high-density virtualized servers. If you're ready to move from 10 to 40 GbE, so is the 15400 Appliance. The Check Point 15400 lets you connect your 10 GbE server uplinks to your 40 GbE core network with up to 4x 40 GbE ports.

TAP THE POWER OF VIRTUALIZATION

Check Point Virtual Systems enable organizations to consolidate infrastructure by creating multiple virtualized security gateways on a single hardware device, offering significant cost savings with seamless security and infrastructure consolidation.

15400 SECURITY APPLIANCE

- 1 Graphic LCD display
- 2 2 x 1 TB RAID1 HDD (optional)
- 3 Three network card expansion slots
- 4 USB ports for ISO installation
- 5 Console port
- 6 Lights-Out Management port
- 7 Sync 10/100/1000Base-T RJ45
- 8 Management 10/100/1000Base-T RJ45



ORDERING INFORMATION

BASE CONFIGURATION ¹	
15400 Next-Gen Threat Prevention bundled with local management for up to 2 gateways	CPAP-SG15400-NGTP
15400 Next-Gen Threat Extraction bundled with local management for up to 2 gateways	CPAP-SG15400-NGTX
HIGH PERFORMANCE PACKAGES ¹	
15400 Next-Gen Threat Prevention High Performance Package with 10x1GbE copper ports, 6x10Gb SFP+ ports, 6xSR transceivers, 2x 1TB HDD and 24 GB of memory	CPAP-SG15400-NGTP-HPP
15400 Next-Gen Threat Extraction High Performance Package with 10x1GbE copper ports, 6x10Gb SFP+ ports, 6xSR transceivers, 2x 1TB HDD and 24 GB of memory	CPAP-SG15400-NGTX-HPP
VIRTUAL SYSTEM PACKAGES	
15400 NGTP appliance with High Performance Package and 10 Virtual Systems	CPAP-SG15400-NGTP-HPP-VS10
A cluster of two 15400 NGTP appliances with High Performance Pack and 10 Virtual Systems	CPAP-SG15400-NGTP-HPP-VS10-2
15400 NGTX appliance with High Performance Package and 10 Virtual Systems	CPAP-SG15400-NGTX-HPP-VS10
A cluster of two 15400 NGTX appliances with High Performance Package and 10 Virtual Systems	CPAP-SG15400-NGTX-HPP-VS10-2

¹ SKUs for 2 and 3 years are available, see the online Product Catalog

ACCESSORIES

INTERFACE CARDS AND TRANSCEIVERS	
8 Port 10/100/1000 Base-T RJ45 interface card	CPAC-8-1C-B
4 Port 1000Base-F SFP interface card; requires additional 1000Base SFP transceivers	CPAC-4-1F-B
SFP transceiver module for 1G fiber ports - long range (1000Base-LX)	CPAC-TR-1LX-B
SFP transceiver module for 1G fiber ports - short range (1000Base-SX)	CPAC-TR-1SX-B
SFP transceiver to 1000 Base-T RJ45 (Copper)	CPAC-TR-1T-B
4 Port 10GBase-F SFP+ interface card	CPAC-4-10F-B
SFP+ transceiver module for 10G fiber ports - long range (10GBase-LR)	CPAC-TR-10LR-B
SFP+ transceiver module for 10G fiber ports - short range (10GBase-SR)	CPAC-TR-10SR-B
2 Port 40GBase-F QSFP interface card	CPAC-2-40F-B
QSFP transceiver module for 40G fiber ports - short range (40GBase-SR)	CPAC-TR-40SR-QSFP-300m
QSFP transceiver module for 40G fiber ports - long range (40GBase-LR)	CPAC-TR-40LR-QSFP-10K
4 Port 1GE copper Bypass (Fail-Open) network interface card (10/100/1000 Base-T)	CPAC-4-1C-BP-B
2 Port 10GE short-range Fiber Bypass (Fail-Open) network interface card (10GBase-SR)	CPAC-2-10-FSR-B-BP

SPARES AND MISCELLANEOUS	
Memory upgrade kit from 8GB to 24GB for 15400 appliance	CPAC-RAM16GB-15400
Additional/Replacement 1 TB hard drive for 15000 and 23000 Appliances	CPAC-HDD-1TB-B
Replacement AC power supply for 15000 Appliances	CPAC-PSU-AC-15000
Replacement fan cartridge for 15000 and 23000 appliances	CPAC-FAN-B
Slide rails for 15000 and 23000 Appliances (22" - 32")	CPAC-RAIL-L
Extended slide rails for 15000 and 23000 Appliances (24" - 36")	CPAC-RAIL-EXT-L

Performance

Production (SecurityPower Benchmark)¹

- 2,600 SecurityPower
- 23 Gbps firewall throughput
- 1.5 Gbps NGTP throughput

Lab (RFC 3511, 2544, 2647, 1242)

- 58 Gbps of firewall throughput, 1518 byte UDP
- 10.8 Gbps of AES-128 VPN throughput
- 2.5 to 7.5 million concurrent connections, 64 byte response²
- 145,000 connections per second, 64 byte response

¹ performance measured with a real-world traffic blend, a typical rule-base, NAT and logging enabled and the most secure threat prevention protection

² performance measured with default/maximum memory

Expansion Options

Base Configuration

- 2 on-board 10/100/1000Base-T RJ-45 ports
- 8x 10/100/1000Base-T RJ-45 IO card
- 2x 10GBaseF SFP+ IO card
- 8 GB memory
- Redundant dual hot-swappable power supplies
- 1x 1TB hard drive
- Lights-Out-Management (LOM)
- Slide rails (22" – 32")

Network Expansion Slot Options (3 Slots)

- 8x 10/100/1000Base-T RJ45 port card, up to 24 ports
- 4x 1000Base-F SFP port card, up to 12 ports
- 4x 10GBase-F SFP+ port card, up to 12 ports
- 2x 40GBase-F QSFP port card, up to 4 ports

Fail-Over Network Options

- 4x 10/100/1000Base-T RJ45 port card
- 2x 10GBase-F SFP+ port card

Virtual Systems

- Max VSs: 25 (w/8GB), 250 (w/24GB)

Routing

Unicast and Multicast Routing (see SK98226)

- OSPFv2 and v3, BGP, RIP
- Static routes, Multicast routes
- Policy-based routing
- PIM-SM, PIM-SSM, PIM-DM, IGMP v2, and v3

Network

Network Connectivity

- 1024 interfaces or VLANs per system
- 4096 interfaces per system (in Virtual System mode)
- 802.3ad passive and active link aggregation
- Layer 2 (transparent) and Layer 3 (routing) mode

High Availability

- Active/Active and Active/Passive - L3 mode
- Session synchronization for firewall and VPN
- Session failover for routing change
- Device and link failure detection
- ClusterXL or VRRP

IPv6

- Features: Firewall, Identity Awareness, Mobile Access, App Control, URL Filtering, IPS, Anti-Bot, Antivirus
- NAT66, NAT64
- CoreXL, SecureXL, HA with VRRPv3

Physical

Power Requirements

- AC Input Voltage: 90-264V
- Frequency: 47-63Hz
- Single Power Supply Rating: 600W
- Power Consumption Maximum: 263W
- Maximum thermal output: 897.4 BTU/hr.

Dimensions

- Enclosure: 2RU
- Standard (W x D x H): 17.4 x 20.84 x 3.5 in.
- Metric (W x D x H): 442 x 529 x 88 mm
- Weight: 14.3 kg (31.5 lbs.)

Operating Environmental Conditions

- Temperature: 32° to 104°F / 0° to 40°C
- Humidity: 5% to 95% (non-condensing)

Storage Conditions

- Temperature: -4° to 158°F / -20° to 70°C
- Humidity: 5% to 95% at 60°C (non-condensing)

Certifications

- Safety: UL60950-1, CB IEC60950-1, CE LVD EN60950-1, TUV GS
- Emissions: FCC, CE, VCCI, RCM/C-Tick
- Environmental: RoHS, *REACH, *ISO14001